

Outdoor Post Lighting Done Right

3" Post Fitter, Fixed Arm — Shown in Turquoise



The #11037/16-1871 delivers reliable, focused post-mount light for pathways, signage, and commercial entries. Streamlined fixed arm, 20½" extension, aluminum construction rated for outdoor use. Shade sizes 10"–16" only. Post tenon adapter available separately. Shown in Turquoise.

LAMP OPTIONS

E26 Socket 60W Max · G25 Bulb Recommended

LED 12 75W Incandescent Equivalent · 120V · Dimmable · 3K or 4K

LED 22 125W Incandescent Equivalent · 120V · Dimmable · 3K or 4K

LED 48 75W Metal Halide Equivalent · 120V · Dimmable · 3K or 4K

LED 88 100W Metal Halide Equivalent · 120V · Dimmable · 3K or 4K

SPECIFICATIONS

Shade Diameter	15½"
Height	12"
Extension	20½"
Mount Type	3" Post Fitter
Arm	Fixed
Post Tenon Adapter	Available separately

IDEAL FOR

- Pathway and walkway lighting
- Signage and monument illumination
- Commercial building entries
- Parking area perimeter lighting
- Hospitality and resort grounds

FINISH OPTIONS

Available in 25+ oven-baked powder coat finishes including White, Black, Almond, Gray, Red, Yellow, Orange, Dark Blue, Navy Blue, Turquoise, Green, Hunter Green, Gold, Bronze Tone, and more. Special colors available on request. Consult the Primelite color chart for the full palette.

*Post tenon adapter available separately.
 See also #11037/16-1864 for twin-arm coverage.*

Shades available in 10", 12", 14", and 16" diameters only. Open bottom. Aluminum construction for outdoor use. For socket fixtures, 60W max; G25 bulbs recommended. LED 12 (75W Inc), 22 (125W Inc), 48 (75W MH), and 88 (100W MH) are 120V, electronic dimming, available in 3K or 4K. LED 48 available on 14"–16" shades only. LED 88 available on 16" shade only. Other LED wattages and additional arm configurations available. 18" and 20" diameter shades available with other arm configurations. Consult color chart for standard powder coat colors. Special colors available on request.