

## Low-Profile, High-Impact: The Flush Mount Edition

15½" Flush Mount Pendant — Shown in Orange



The #11037/16F brings the iconic RLM shade to low-clearance ceilings with a clean 5" flush mount profile. At just 5" tall it's ideal for covered patios, tight interiors, and any space where pendant stems won't fit. Shown in Orange — available in 25+ powder coat finishes.

### LAMP OPTIONS

**E26 Socket** 60W Max · G25 Bulb Recommended

**LED 12** 75W Incandescent Equivalent · 120V · Dimmable · 3K or 4K

**LED 22** 125W Incandescent Equivalent · 120V · Dimmable · 3K or 4K

**LED 48** 75W Metal Halide Equivalent · 120V · Dimmable · 3K or 4K

**LED 88** 100W Metal Halide Equivalent · 120V · Dimmable · 3K or 4K

### SPECIFICATIONS

Shade Diameter	15½"
Height	5"
Mount Type	Flush Mount
Construction	Aluminum, Outdoor Rated
Finish Shown	Orange

### IDEAL FOR

- Covered patios and low-ceiling porches
- Tight interior spaces and utility rooms
- Retail and hospitality areas
- Residential garages and outbuildings

### FINISH OPTIONS

Available in 25+ oven-baked powder coat finishes including White, Black, Almond, Gray, Red, Yellow, Orange, Dark Blue, Navy Blue, Turquoise, Green, Hunter Green, Gold, Bronze Tone, and more. Special colors available on request. Consult the Primelite color chart for the full palette.

Shades available in 10", 12", 14", 16", 18", and 20" diameters. Open bottom. Aluminum construction for outdoor use. For socket fixtures, 60W max; G25 bulbs recommended. LED 12 (75W Inc), 22 (125W Inc), 48 (75W MH), and 88 (100W MH) are 120V, electronic dimming, available in 3K or 4K. LED 48 available on 14"–20" shades only. LED 88 available on 16"–20" shades only. Other LED wattages are available. Consult color chart for standard powder coat colors. Special colors available on request.